



VMware

2V0-622 Exam

VMware Data Center Virtualization Exam

Thank you for Downloading 2V0-622 exam PDF Demo

You can Buy Latest 2V0-622 Full Version Download

<https://www.certkillers.net/Exam/2V0-622>

<https://www.certkillers.net>

Version: 18.0

Question: 1

Which are two supported storage primitives for VAAI NAS? (Choose two.)

- A. block zeroing
- B. Reserve Space
- C. hardware assisted locking
- D. Full File Clone

Answer: AC

Question: 2

Which two choices are applicable to vSphere Availability? (Choose two.)

- A. Admission Control
- B. Heartbeat Datastores
- C. VM Startup/Shutdown
- D. Power Management

Answer: AB

Question: 3

What are three considerations when booting ESXi host from SAN using software FCoE? (Choose three.)

- A. The VMware_FCoE_vSwitch that the installer automatically created cannot be changed.
- B. Boot LUN cannot be shared with other hosts even on shared storage.
- C. Multipathing is not supported at pre-boot.
- D. Software FCoE boot configuration cannot be changed from within ESXi

Answer: BCD

<https://kb.vmware.com/s/article/2032363>

Question: 4

Which two statements correctly describe VM-VM affinity rules? (Choose two.)

- A. vSphere DRS attempts to keep the virtual machines together on the same ESXi host.
- B. When two VM-VM affinity rules conflict, the older one takes precedence and the newer rule is

disabled.

C. vSphere DRS attempts to keep the virtual machines on separate ESXi hosts.

D. When two VM-VM affinity rules conflict, the newer one takes precedence and the older rule is disabled.

Answer: AB

Question: 5

Which port is used for vSphere HA agent-to-agent communication?

A. 902

B. 443

C. 8182

D. 22

Answer: C

Question: 6

In which scenario will vSphere DRS balance resources when set to Fully Automated?

A. Hosts with shared or non-shared storage

B. Hosts with only shared storage

C. Hosts are part of a vSphere HA cluster

D. Power Management is set to Balanced on hosts

Answer: B

Question: 7

The Health Check feature in the vSphere Distributed Switch helps troubleshoot network connectivity. What three checks does this feature perform? (Choose three.)

A. Network Utilization

B. MTU

C. VLAN

D. Teaming and Failover

Answer: BCD

<https://kb.vmware.com/s/article/2032878>

Question: 8

An administrator must collect diagnostic information following a failed ESXi host upgrade. Which

command should the administrator run?

- A. vm-support
- B. Get-Esxtop
- C. vicfg-syslog
- D. esxtop -R vm-support_dir_path

Answer: A

Question: 9

An ESXi host's VMCA-Signed certificate has expired. How can the certificate be renewed?

- A. In the vSphere Web Client, browse to the host in question. Click the Manage tab and select settings. Select System and click Certificate, then click the Renew button.
- B. In the vSphere Web Client, browse to the host in question. Click the Manage tab and select settings. Select System and click Certificate, then click the Refresh CA Certificates button.
- C. Run the command /sbin/generate-certificates on the affected host.
- D. Disconnect the host from vCenter Server and reconnect it.

Answer: D

Explanation:

You can renew your certificates when they are about to expire, or if you want to provision the host with a new certificate for other reasons. If the certificate is already expired, you must disconnect the host and reconnect it.

Question: 10

Which is the correct order for upgrading vSphere components?

- A. vCenter Server, ESXi hosts, VMware Tools, Virtual Machine hardware
- B. VMware Tools, Virtual Machine hardware, ESXi hosts, vCenter Server
- C. vCenter Server, Virtual Machine hardware, VMware tools, ESXi hosts
- D. ESXi hosts, vCenter Server, Virtual Machine hardware, VMware Tools

Answer: A

Explanation:

Correct order is:

- 1 Back up your configuration
- 2 Upgrade vCenter Server
- 3 Upgrade ESXi hosts
- 4 Upgrade virtual machines and virtual appliances

Question: 11

Which two datastore types are supported by Storage I/O Control v2? (Choose two.)

- A. vSAN
- B. RDM
- C. NFS
- D. Virtual Volumes
- E. VMFS

Answer: C, E

Question: 12

Which iSCSI initiator type can be used with any network interface card?

- A. Software iSCSI initiator
- B. Software FCoE adapter
- C. Hardware Independent iSCSI initiator
- D. Hardware Dependent iSCSI initiator

Answer: A

Explanation:

A software iSCSI adapter is a VMware code built into the VMkernel. It allows your host to connect to the iSCSI storage device through standard network adapters. The software iSCSI adapter handles iSCSI processing while communicating with the network adapter. With the software iSCSI adapter, you can use iSCSI technology without purchasing specialized hardware.

Question: 13

An administrator is attempting to power on a virtual machine with 32GB of memory. The operation fails with the following error:

Could not power on VM: No space left on device

Checking the space on the virtual machine's datastore, there is 30GB free.

Which action would allow the VM to power on?

- A. Set a 2GB memory reservation on the VM.
- B. Mount the virtual disk from the affected VM on to another virtual machine and free up space from within the OS.
- C. Enable vSphere HD admission control on the cluster in which the VM resides.
- D. Set a 2GB memory limit on the VM.

Answer: A

Explanation:

The swap file size can be calculated with the formula (.vswp File = Allocated Memory - Memory Reservation).

As per default, the reservation is set to 0, so the .vswp file size is equal to the amount of virtual memory.

Question: 14

When using “Cluster resource percentage” for host failover capacity in vSphere HA Admission Control, the total resource requirements are calculated from which two values? (Choose two.)

- A. Total vCPUs assigned to each VM.
- B. Average CPU usage on each VM over time.
- C. Memory reservations on each VM.
- D. Total memory assigned to each VM.
- E. Average active memory on each VM over time.
- F. CPU reservations on each VM.

Answer: C,F

Question: 15

Which are four attributes of the Active vCenter HA node? (Choose four.)

- A. It uses the vCenter HA network to communicate with the Witness node.
- B. It constantly replicates vPostgres data with the Witness node.
- C. It uses a public IP address for the management interface.
- D. It runs the active vCenter Server Appliance instance.
- E. It uses the vCenter HA network for replication of data.
- F. It provides a quorum to protect against split-brain situations.

Answer: A, C, D, E

Explanation:

Active

- Runs the active vCenter Server Appliance instance
- Uses a public IP address for the management interface
- Uses the vCenter HA network for replication of data to the Passive node
- Uses the vCenter HA network to communicate with the Witness node

Question: 16

Which are two vCenter Server two-factor authentication methods? (Choose two.)

- A. RSA SecurID
- B. Smart Card
- C. SAML

D. Symantec VIP

Answer: A, B

CertKillers.net

Thank You for trying 2V0-622 PDF Demo

To Buy Latest 2V0-622 Full Version Download visit link below

<https://www.certkillers.net/Exam/2V0-622>

Start Your 2V0-622 Preparation

[Limited Time Offer] Use Coupon “CKNET” for Further discount on your purchase. Test your 2V0-622 preparation with actual exam questions.

<https://www.certkillers.net>