

## **Alcatel lucent**

4A0-105 Exam

**Alcatel-Lucent Virtual Private LAN Services** 

Thank you for Downloading 4A0-105 exam PDF Demo

You can Buy Latest 4A0-105 Full Version Download

https://www.certkillers.net/Exam/4A0-105

Which of the following technologies allows for two explicit VLAN tags to be received from a custome device?  A. RSVP-TE B. SP-VLAN C. QinQ D. Dot1Q  Answer: C  Question: 2  What is the SA in the Ethernet frame used for by a layer 2 switch?  A. MAC learning B. SA filtering C. Routing table population D. Frame forwarding	mer
device?  A. RSVP-TE B. SP-VLAN C. QinQ D. Dot1Q  Answer: C  Question: 2  What is the SA in the Ethernet frame used for by a layer 2 switch?  A. MAC learning B. SA filtering C. Routing table population D. Frame forwarding	
B. SP-VLAN C. QinQ D. Dot1Q  Answer: C  Question: 2  What is the SA in the Ethernet frame used for by a layer 2 switch?  A. MAC learning B. SA filtering C. Routing table population D. Frame forwarding	
C. QinQ D. Dot1Q  Answer: C  Question: 2  What is the SA in the Ethernet frame used for by a layer 2 switch?  A. MAC learning B. SA filtering C. Routing table population D. Frame forwarding	
D. Dot1Q  Answer: C  Question: 2  What is the SA in the Ethernet frame used for by a layer 2 switch?  A. MAC learning B. SA filtering C. Routing table population D. Frame forwarding	
Answer: C  Question: 2  What is the SA in the Ethernet frame used for by a layer 2 switch?  A. MAC learning B. SA filtering C. Routing table population D. Frame forwarding	
Question: 2  What is the SA in the Ethernet frame used for by a layer 2 switch?  A. MAC learning B. SA filtering C. Routing table population D. Frame forwarding	
What is the SA in the Ethernet frame used for by a layer 2 switch?  A. MAC learning B. SA filtering C. Routing table population D. Frame forwarding	
What is the SA in the Ethernet frame used for by a layer 2 switch?  A. MAC learning B. SA filtering C. Routing table population D. Frame forwarding	
A. MAC learning B. SA filtering C. Routing table population D. Frame forwarding	
B. SA filtering C. Routing table population D. Frame forwarding	
C. Routing table population  D. Frame forwarding	
D. Frame forwarding	
Answer: A	
Question: 3	
What are the limitations of a traditional layer 2 switch? (Choose 3)	
A. Isolates collision domains.	
B. Requires layer 2 loop prevention.	
C. Slow response to topology changes.	
D. Limited to 4094 vlans per switch.	
E. Increased flooding.	
Answer: BCD	

Which of the following statements about the VC-ID is false?

- A. The vc-id is signaled in the control plane.
- B. The vc-id is part of the data plane encapsulation.
- C. There is a vc-id to vc-label mapping.

Question: 4

D. The vc-id has point to point significance.

	Answer: B
Question: 5	
Assuming TLDP and RSVP are both being used in an MPLS network statements is true?	core which of the following
A. TLDP is used to create the inner label, RSVP is used to create the out. B. TLDP is used to create the outer label, RSVP is used to create the inner. C. TLDP and RSVP cannot be used in the same network since they both D. When RSVP is used, TLDP must be disabled and static vc labels should be the create either labels based on how the	er label. provide the same label. d be used.
	Answer: A
Question: 6	O.
Fill in the blank for this next sentence. Flooded traffic received on any replicated to other spoke SDPs and SAPs and not transmitted on any me	
A. Spoke SDP B. Mesh SDP A. Either (a) or (b) will make this sentence true. D. Neither (a) nor (b) will make this sentence true.	
	Answer: B

## Thank You for trying 4A0-105 PDF Demo

To Buy Latest 4A0-105 Full Version Download visit link below

https://www.certkillers.net/Exam/4A0-105

## Start Your 4A0-105 Preparation

[Limited Time Offer] Use Coupon "CKNET" for Further discount on your purchase. Test your 4A0-105 preparation with actual exam questions.