



Cisco

650-294

TelePresence Video Field Engineer for(R) Express

QUESTION: 44

Which two ways can individual participants change their screen layout without affecting other participants? (Choose two.)

- A. by moving the participant into a different meeting using the web interface
- B. by the nominated chair endpoint using FECC
- C. via the conference settings in the web interface
- D. by the participant using FECC
- E. via the participant settings in the web interface

Answer: C, D

QUESTION: 45

You want to obtain specific configuration details from each of the systems that are registered to your Cisco TelePresence Management Suite. Where can you do this?

- A. Choose Navigator from the Systems menus.
- B. Choose System Overview from the Systems menus.
- C. Run System Tracking from the Systems menus.
- D. Connect to the Cisco TelePresence Management Suite via a console connection and use show commands.

Answer: A

QUESTION: 46

Which tool would you use to set predefined configurations for one or more systems in Cisco TelePresence Management Suite?

- A. Ticketing System from the Systems menu
- B. Templates from the Provisioning menu
- C. Configuration Backup from the Systems menu
- D. Directory screen from the Provisioning menu

Answer: B

QUESTION: 47

What does the interworking feature provide?

- A. SIP to H.320 gateway functionality
- B. SIP to H.323 gateway functionality

- C. IPv4 to IPv6 gateway functionality
- D. firewall traversal

Answer: B

QUESTION: 48

In SIP configuration, what needs to match in both the Cisco TelePresence VCS configuration and the endpoint configuration?

- A. DNS server
- B. supported video protocols
- C. SIP domain
- D. service prefix

Answer: C

QUESTION: 49

Which service must be enabled to set up Cisco TelePresence Movi users on a Cisco TelePresence VCS Expressway Starter Pack?

- A. Interworking
- B. Multiway
- C. H.323
- D. SIP

Answer: D

QUESTION: 50

What effect does the prefix for Cisco TelePresence MCU registrations have on Cisco TelePresence MCU registration?

- A. The prefix is placed in front of all E.164 aliases.
- B. Anything that is dialed with the prefix will be routed to the Cisco TelePresence.
- C. The prefix is placed in front of all SIP URIs.
- D. The prefix replaces the domain if the prefix is dialed.

Answer: B

Download Full Version From <https://www.certkillers.net>



DON'T KNOW
OR NO PREFERENCE

Pass your exam at First Attempt....Guaranteed!