



IBM

A2090-612

Accessment: DB2 10 DBA for z/OS Assessment

QUESTION: 123

Using the -SET LOG command, what logging characteristics CANNOT be modified?

- A. The number of minutes between the start of successive checkpoints.
- B. Add a newly defined active log data set to the active log inventory.
- C. Altering DB2 from dual active logging mode to single active logging mode.
- D. The number of log records that DB2 writes between the start of successive checkpoints.

Answer: C

QUESTION: 124

In a data sharing environment, how is the LRSN value created?

- A. It is selected from the DB2 catalog.
- B. It is generated from a sequence object.
- C. It is derived from the sysplex timer (store clock).
- D. It is derived from combining RBAs from multiple members.

Answer: C

QUESTION: 125

What kind of information is stored in SYSIBM.SYSCOPY?

- A. General information needed for recovery.
- B. Only information about existing image copies.
- C. Information about currently running and stopped copy jobs.
- D. Only information about objects which are currently in copy pending.

Answer: A

QUESTION: 126

What is one of the first key steps in preparing to use the BACKUP SYSTEM utility?

- A. Run the MODIFY RECOVERY utility.
- B. Alter the BSDS to allow BACKUP SYSTEM.
- C. Define one or more storage groups to a COPYPOOL.
- D. Stop DB2 to enable DFSMSHsm functionality to be used.

Answer: C

QUESTION: 127

An object (table space, index space or a physical partition of a table space or index space) is in AREST or RESTP status. If backout activity is not already underway, what should occur?

- A. Issue a RECOVER POSTPONED command.
- B. Issue a START command with ACCESS(RW).
- C. Recycle the system with the system parameter LBACKOUT=NO.
- D. Issue a STOP command and then a START command with ACCESS(RW).

Answer: A

QUESTION: 128

When planning for disaster recovery, which two items are NOT required to send to the remote site? (Choose two.)

- A. DB2 archive logs.
- B. Image copies of indexes.
- C. A copy of your ICF catalog.
- D. Image copies of table spaces.
- E. Backups of the DB2 catalog and directory.

Answer: B, C

QUESTION: 129

Which two parameters would reduce the impact of availability from a REORG with SHRLEVEL CHANGE for a partitioned table space with 16 parts? (Choose two.)

- A. LOG NO
- B. SORTKEYS 16
- C. FASTSWITCH YES
- D. AUTOESTSPACE YES
- E. DRAIN_WAIT & RETRY

Answer: C, E

QUESTION: 130

The application will be handling a large volume of input data that will need to be added to or update 4 different tables. On average, there will be 50 million input records daily. To ensure that the application process to SQL INSERT and SQL UPDATE(or SQL MERGE) delivers a high level of availability to the tables involved in this application process, what is a key component of the application coding?

- A. Issue a LOCK TABLE for all 4 tables.
- B. Execute the SQL INSERT before the SQL UPDATE.
- C. Provide an effective commit / restart process.
- D. Run a QUIESCE utility before the process starts.

Answer: C

QUESTION: 131

For monitoring space growth over time, which statistics should NOT be considered?

- A. SYSIBM.SYSTABLEPART_HIST CARDF, SPACEF
SYSIBM.SYSINDEXPART_HIST CARDF, SPACEF
- B. SYSIBM.SYSTABLEPART CARDF, SPACEF
SYSIBM.SYSINDEXPART CARDF, SPACEF
- C. SYSIBM.SYSTABLESPACE DSSIZE, AVGWLEN
SYSIBM.SYSINDEXES PIECESIZE, AVGKEYLEN
- D. SYSIBM.SYSTABLESPACESTATS SPACE
SYSIBM.SYSINDEXSPACESTATS SPACE

Answer: C

QUESTION: 132

Which option allows the UNLOAD utility to unload LOBs into output files together with non-LOB data?

- A. DELIMITED
- B. SPANNED YES
- C. DSNTYPE HFS on the TEMPLATE
- D. DSNTYPE LIBRARY or PDS on the TEMPLATE

Answer: B

QUESTION: 133

Which of the following statements is NOT correct?

- A. UNLOAD with NOPAD improves performance.
- B. Partition parallelism in UNLOAD is activated with STACK(YES) and UNIT(TAPE).
- C. Unload will process cloned table with UNLOAD CLONE and CLONED YES on the LISTDEF.
- D. Clone table allows replacing data without renames and rebinds to support online load replace.

Answer: B

QUESTION: 134

If a ROWID column is defined on a table as GENERATED BY DEFAULT, what must also be done?

- A. Nothing because DB2 will control the values.
- B. A unique index must be defined on the ROWID column.
- C. An identity column must also be created to control uniqueness.
- D. Extra space must be allocated for an overflow area in the table space.

Answer: B

Download Full Version From <https://www.certkillers.net>



DON'T KNOW
OR NO PREFERENCE

Pass your exam at First Attempt....Guaranteed!