

IBM

C2150-202

IBM Security Access Manager for Mobile V8.0 Implementation

Answer: B, E

QUESTION: 65

Which two elements can be shown in the output of an IBM SECURITY CBA AUDIT RTE event? (Choose two.)

- A. majorStatus
- B. minorStatus
- C. appUserName
- D. globallnstanceld
- E. restManagement
- F. RESTInvocationURI

Answer: C, D

Reference:

http://www-

01.ibm.com/support/knowledgecenter/SSELE6_8.0.0.5/com.ibm.isam.doc_8.0.0.5/a udit/ref/ ref_security_cba_audit_rte_events.html

QUESTION: 66

Where would you browse in the ISAM for Mobile GUI to manually enable trace?

- A. Monitor Analysis and Diagnostics > Logs > Runtime Tracing
- B. Monitor Analysis and Diagnostics > Logs > Runtime Logging
- C. Secure Mobile Settings > Manage > Runtime Parameters > Runtime Status
- D. Secure Mobile Settings > Manage > Runtime Parameters > Runtime Logging

Answer: D

QUESTION: 67

Which two audit event types record actions such as creation of risk profiles and device registration? (Choose two.)

- A. IBM_SECURITY_RUNTIME_MGMT
- B. IBM_SECURITY_CBA_AUDIT_RTE
- C. IBM_SECURITY_CBA_AUDIT_MGMT
- D. IBM_SECURITY_CBA_AUDIT_AUTHZ
- E. IBM_SECURITY_RTSS_AUDIT_MGMT

Answer: C, ?

Reference:

http://www-01.ibm.com/support/docview.wss?uid=swg27042973&aid=12(p.29)

QUESTION: 68

When you use the web based (LMI) installation wizard, how does the appliance get the initial IP address of the management interface?

- A. Provided through DHCP
- B. Specified manually in the installation wizard
- C. Input through a keyboard on the front panel of the appliance
- D. Specified manually through a terminal connected to the appliance

Answer: B

QUESTION: 69

When configuring one-time password in ISAM for Mobile. Customer A's requirements are to use a provider that generates a one-time password by using a specified algorithm with a time-based one-time password application. Which provider is configured to meet customer A's one-time password requirements?

- A. RSA
- B. MAC
- C. TOTP
- D. HOTP

Answer: C

Reference:

erence:http://www-

 $01.ibm.com/support/knowledgecenter/SSELE6_8.0.0/com.ibm.ammob.doc_8.0/concept/otp.html (see TOTP)$

OUESTION: 70

The Appliance Dashboard shows a high-level view of current operations and statistics. One of these statistics is the current CPU activity. Which set of steps is used if the CPU activity of a hardware appliance shows constant use and averages above sixty percent?

- A. Review the current trace level, the number of policies, and the use of PIPs. Then, add another CPU to the redundant CPU slot.
- B. Review the current trace level, the number policies, and the use of PIPs. Then, increase capacity by adding another hardware appliance.
- C. Disable all traces, clear out all logs, and switch partitions to allow the primary partition to be defragmented. Then, update the CPU to the latest current supported architecture.
- D. Disable all traces, clear out all logs, and switch partitions to allow the primary partition to bedefragmented. Then, purchase and load the Enterprise CPU Feature key to enable the secondary CPU.

Answer: C

Download Full Version From https://www.certkillers.net

















