



IBM

C2180-374

IBM WebSphere MQ V7.0 System Administration

Answer: A

QUESTION: 152

Which of the following statements about persistent messages is correct? Persistent messages:

- A. are always written to a log
- B. should always be used no matter the data is critical or not.
- C. can survive a queue manager restart but not a system failure
- D. cannot be stored in the same queue with nonpersistent messages

Answer: C

QUESTION: 153

A company wants to use SYSTEM.DEAD.LETTER.QUEUE as the dead letter queue name on all queue managers on their Solaris platforms. Which of these actions will implement that policy?

- A. Add the line DeadLetterQueue=SYSTEM.DEAD.LETTER.QUEUE to the AllQueueMangaers stanza of lvarlmqs.ini before running crtmqm
- B. Set the environment variable MQS_DEFAULT_DLQ to SYSTEM.DEAD.LETTER.QUEUE before running crtmqm
- C. Run crtmqm without specifying any options.
- D. Specify the option “-u SYSTEM.DEAD.LETTER.QUEUE” when running the crtmqm command.

Answer: D

QUESTION: 154

An administrator has been asked to create a model queue that will be used by client applications to receive reply messages from a central processing application on a distinct queue for each client application. The messages returned to the client are persistent messages. What command is appropriate to define the model queue?

- A. DEFINE QMODEL (RPLYQ) DEFPRESP (YES)
- B. DEFINE QMODEL (RPLYQ) DEFPRESP (YES)
- C. DEFINE QMODEL (RPLYQ) DEFPRESP (PERMDYN)
- D. DEFINE QMODEL (RPLYQ) DEFPRESP (TEMPDYN)

Answer: B

QUESTION: 155

A central manager on Solaris machine hosting several enterprise applications is connected to several other queue managers in a network. Each channel should be started automatically whenever there is a message for that channel to transmit? What is the best way to achieve this?

- A. Start a number of channel initiator processes equal to the number of channels.
- B. Edit the qm.ini file for stanza MAXINITIATORS = the number of channels to be started
- C. Modify trigger interface to start all channels automatically
- D. Modify the transmission queue of each channel to include the corresponding channel name in the trigger data attribute and the initiation queue as SYSTEM.CHANNEL.INITQ

Answer: D

QUESTION: 156

A WebSphere MQ server is installed on Windows. The INITIAL_CONTEXT_FACTORY is set to com.ibm.jndi.fscontext.RefFSContextFactory in the JMSAdmin.conf file. After an administrator successfully executes a series of commands using JMSAdmin facility to create JMS objects, which of the following statements is true?

- A. LDAP server is used
- B. A DB2 database is used
- C. A queue manager is created
- D. A file named .bindings is created

Answer: D

QUESTION: 157

A company has a heterogeneous MQ infrastructure. What feature of MQ Explorer V7.0 can be used to categorize by platform and simultaneously all the queue managers running on a particular platform?

- A. Queue manager filtering
- B. Queue manager clustering
- C. Queue manager sharing group
- D. Queue manager sets

Answer: C

Download Full Version From <https://www.certkillers.net>



DON'T KNOW
OR NO PREFERENCE

Pass your exam at First Attempt....Guaranteed!