

**IBM** 

C2180-410

IBM MQ V8.0 System Administration

D. Set the queue manager and the queue STATQ(ON) attributes, and the interval in the queue manager attribute STATINT(900).

**Answer:** A

**QUESTION:** 52

A system administrator would like to capture accounting and statistics data to analyze performance of channels across multiple platforms. Where can the system administrator capture the data?

- A. In the System Management Facility (SMF).
- B. On SYSTEM.ADMIN.PERFM.EVENT queue.
- C. On SYSTEM.ADMIN.ACCOUNTING.QUEUE and SYSTEM.ADMIN.STATISTICS.QUEUE.
- D. On SYSTEM.ADMIN.ACCOUNTING.QUEUE and SYSTEM.ADMIN.STATISTICS.QUEUE for distributed platforms and in System Management Facility (SMF) for the z/OS platform.

**Answer:** C

**Reference:** 

http://www-01.ibm.com/support/docview.wss?uid=swg21377808

## **QUESTION:** 53

An MQI Client application, which is run from different client machines, wants to benefit from the read ahead performance advantages for non-persistent messages.

While the client programs are changed on some machines to specify the MQOO\_READ\_AHEAD option, some other machines have to run the existing client application code without that option for a certain period of time. What must the system administrator configure to support the coexistence of the two different versions of the client application?

A. SHARECNV(0) on the SVRCONN channel and DEFREADA(YES) for the queues

B. SHARECNV(>0) on the SVRCONN channel and DEFREADA(NO) for the queues

C. SHARECNV(>0) on the SVRCONN channel and DEFREADA(YES) for the queues

D. SHARECNV(>1) on the SVRCONN channel and DEFREADA(ENABLED) for the queues

#### **Answer:** A

#### **Reference:**

ftp://public.dhe.ibm.com/software/integration/support/supportpacs/individual/mp1h.p df

**QUESTION: 54** 

A system administrator needs to tune a SVRCONN channel for performance. Currently, the channel shared conversation attribute, SHARECNV, has the default value. To ensure performance enhancement, including the V8.0 distributed server performance improvement, what value does the system administrator need to set the SHARECNV attribute to?

- A. 0
- B. 1
- C. 20
- D. 999999999

**Answer:** D

### **QUESTION:** 55

A client application receives en error MQRC\_Q\_FULL indicating that the queue is full. The administrator sets the queue properties for queue depth max events (QDPMAXEV) to ENABLED. Which setting must the system administrator configure at the queue manager level and which queue does the system administrator need to monitor for event messages?

A. Inhibit Events set to Enabled Monitor the SYSTEM.ADMIN.INHIBIT.EVENT queue

B. Remote Events set to Enabled Monitor the SYSTEM.ADMIN.QMGR.EVENT queue

C. Performance Events set to Enabled Monitor the SYSTEM.ADMIN.PERFM.EVENT queue

D. Configuration Events set to Enabled Monitor the SYSTEM.DEFAULT.MODEL.QUEUE queue

**Answer:** C

**QUESTION:** 56

A system administrator needs to ensure that MQ activity messages are created for an application message as it is routed through MQ network. What must the system administrator verify? (choose 3)

A. The application has PUT authority to the activity message queues.

B. The application message specifies that activity reports are to be generated.

C. The MCA channels have been restarted after the configuration changes were made.

D. Activity recording is enabled on every queue manager in the network.

E. MQI statistics monitoring is enabled on every queue manager in the network.

F. Queue manager events are enabled for every queue manager in the network.

**Answer:** B, C, E

## **QUESTION:** 57

A system administrator is planning to enable events when queue manager objects are created, changed or deleted. Which events should the system administrator enable?

- A. Logger
- B. Performance
- C. Configuration
- D. Queue Manager

**Answer:** C

# Download Full Version From https://www.certkillers.net

















