



EMC

E20-307 Exam

**Prepare for EMC VMAX3 Solutions Specialist Exam for
Implementation Engineers**

Thank you for Downloading E20-307 exam PDF Demo

You can Buy Latest E20-307 Full Version Download

<https://www.certkillers.net/Exam/E20-307>

<https://www.certkillers.net>

Version: 8.0

Question: 1

Please check the option that best describes your relationship with Dell EMC:

- A. Dell EMC Employee
- B. Dell EMC Customer/Partner
- C. Other

Answer: C

Question: 2

CORRECT TEXT

Please enter your Powerlink Username below. If you do not have a Powerlink Username or do not know your Powerlink Username enter none.

Powerlink Username:

Answer: Varies

Question: 3

What are pre-configured in VMAX3 and VMAX All Flash arrays?

- A. SRDF devices
- B. Gatekeeper devices
- C. Thin devices
- D. Data devices

Answer: C

Question: 4

A TimeFinder SnapVX snapshot of source volumes has been linked to target volumes. The target volumes are being used for application testing. What should be done prior to a relink operation?

- A. Continue accessing the source volumes, stop accessing the target volumes.
- B. Continue accessing the source and target volumes.
- C. Stop accessing the source and target volumes.
- D. Stop accessing the source volumes, continue accessing the target volumes

Answer: A

Question: 5

A VMAX3 parent Storage Group (SG) contains two child SGs: SG1 and SG2. What is a valid bandwidth limit setting for this cascaded Storage Group?

- A. Parent SG – 400; SG1 – 500; SG - 200
- B. Parent SG – 400; SG1 – 500; SG - NOLIMIT
- C. Parent SG – 500; SG1 – 500; SG - 400
- D. Parent SG – 500; SG1 – NOLIMIT; SG - 1000

Answer: C

Question: 6

At which levels are FAST performance metrics collected in a VMAX3 array?

- A. Disk Group, Storage Group, and thin device sub-LUN
- B. Data Pool, Storage Resource Pool, and Storage Group
- C. Disk Group, Data Pool, and thin device sub-LUN
- D. Disk, Data Pool, and Storage Resource Pool

Answer: A

Question: 7

DRAG DROP

What is the correct sequence of actions performed by a VMAX3 when the SRDF failback command is executed?

| | |
|----------------------------------|--------|
| Read/Write enable the R1 devices | STEP 1 |
| Merge the device track tables | STEP 2 |
| Suspend the RDF links | STEP 3 |
| Write disable the R2 devices | STEP 4 |
| Resume the RDF links | STEP 5 |

Answer:

| | |
|----------------------------------|----------------------------------|
| Read/Write enable the R1 devices | Write disable the R2 devices |
| Merge the device track tables | Suspend the RDF links |
| Suspend the RDF links | Merge the device track tables |
| Write disable the R2 devices | Resume the RDF links |
| Resume the RDF links | Read/Write enable the R1 devices |

Question: 8

Which Solutions Enabler environment variable can be set to stop the user from getting asked for confirmation during command execution?

- A. symcli_noprompt
- B. symcli_command_scope
- C. symcli_mode
- D. symcli_output_mode

Answer: A

Explanation:

Reference:

<https://www.emc.com/collateral/TechnicalDocument/docu46983.pdf> (page 243)

CertKillers.net

Thank You for trying E20-307 PDF Demo

To Buy Latest E20-307 Full Version Download visit link below

<https://www.certkillers.net/Exam/E20-307>

Start Your E20-307 Preparation

[Limited Time Offer] Use Coupon “CKNET” for Further discount on your purchase. Test your E20-307 preparation with actual exam questions.

<https://www.certkillers.net>