



# Extreme Networks

EW0-200 Exam

**Extreme Networks Associate Exam**

Thank you for Downloading EW0-200 exam PDF Demo

You can Buy Latest EW0-200 Full Version Download

<https://www.certkillers.net/Exam/EW0-200>

<https://www.certkillers.net>

---

**Question: 1**

---

Which CLI command would you use to create a default route with a metric of 5 and a gateway of 10.0.0.1?

- A. CONFIG IPRROUTE ADD DEFAULT 10.0.0.1 5
- B. CONFIG IPRROUTE ADD DEFAULT 5 10.0.0.1
- C. CREATE IPRROUTE ADD DEFAULT 10.0.0.1 5
- D. CREATE IPRROUTE ADD DEFAULT 5 10.0.0.1

---

**Answer: A**

---

---

**Question: 2**

---

An Extreme Switch is shipped with a pre-configured VLAN called DEFAULT that has all switch ports as tagged members.

- A. TRUE
- B. FALSE

---

**Answer: B**

---

---

**Question: 3**

---

How would you stop a scheduled configuration download from happening? Use the CLI command

- A. cancel configuration download
- B. download configuration cancel
- C. configuration download cancel
- D. delete configuration download

---

**Answer: B**

---

---

**Question: 4**

---

Exhibit: Given the information in the exhibit, select the option that would allow you to change the active ExtremeWare version to 6.1.9b11 upon reboot.

```
sysName:          Summit5iTx
sysLocation:
sysContact:       support@extremenetworks.com, +1 888 257 3000
System MAC:       00:01:30:97:F1:00

License:          Full L3 + Security.
System Mode:      802.1Q EtherType is 8100 (Hex).  CPU Tx-Priority=High
Recovery Mode:    none
Random Early Drop Probability: 0
DLCS:             disabled
Current time:     Thu Feb 28 15:37:30 2002
Timezone:         [Auto DST Enabled] GMT Offset: 0 minutes, DST is not in effect.
Boot time:        Thu Feb 28 14:07:06 2002
Next reboot:      None scheduled
Timed upload:     None scheduled
Timed download:   None scheduled
Temperature:      Normal. All fans are operational.
Power Supply:     PSU-A OK, PSU-B

Software Image Selected :      secondary
Software Image booted :       secondary
Primary Software version:      6.1.5b11
Secondary software version:     6.1.7b9

Configuration selected:        primary
Configuration booted:          primary
Primary configuration:         Empty
Secondary configuration:        Empty
```

- A. use image primary
- B. download config primary
- C. use config primary
- D. download image primary

---

**Answer: A**

---

---

### Question: 5

---

The default administrator login name for a new Extreme switch was entered as ADMIN (all caps). This will allow the administrator access to the CLI.

- A. TRUE
- B. FALSE

---

**Answer: B**

---

---

### Question: 6

---

ExtremeWare, pre-installed on every Extreme Networks ?chipset switch, combines industry standard protocols to ensure interoperability with legacy switches and routers, QoS for bandwidth management and traffic prioritization in today networks.

- A. TRUE
- B. FALSE

---

**Answer: A**

---

---

### Question: 7

---

Which step would you take to configure a VLAN to only allow IP-related traffic?

- A. config <vlan> protocol ip
- B. config protocol <vlan> ip
- C. config ip protocol <vlan>
- D. None of these.

---

**Answer: A**

---

---

**Question: 8**

---

Extreme Networks switches build their forwarding database from the incoming packet field information containing the

- A. Source MAC address.
- B. Destination MAC address.
- C. Source IP address.
- D. Destination IP address.

---

**Answer: A**

---

---

**Question: 9**

---

The CLI console port utilizes a serial cable for physical switch to terminal connection.

- A. TRUE
- B. FALSE

---

**Answer: A**

---

---

**Question: 10**

---

Which CLI command will you use to change the CLI prompt from the default display to Switch02?

- A. CONFIG SNMP SYSLOCATION Switch02
- B. CONFIG SNMP SYSNAME Switch02
- C. CONFIG CLI PROMPT Switch02
- D. CONFIG CLI DISPLAY Switch02

---

**Answer: B**

---

---

**Question: 11**

---

In spanning tree, the designated bridge is the bridge with the

- A. least-cost path to the root bridge
- B. highest bridge priority
- C. lowest port cost on all ports
- D. None of these

---

**Answer: A**

---

---

**Question: 12**

---

In ExtremeWare, active VLANs that are configured with ports and an IP address and configured to forward IP and run a routing protocol will have their subnet advertised.

- A. TRUE
- B. FALSE

---

**Answer: A**

---

---

**Question: 13**

---

A 802.1Q tag is a marker inserted between the source and destination MAC addresses fields of the Ethernet frame.

- A. TRUE
- B. FALSE

---

**Answer: B**

---

---

**Question: 14**

---

Which of the following protocol filter/s is/are predefined in ExtremeWare?

- A. OSPF
- B. TCP
- C. NETBIOS
- D. All of these

---

**Answer: C**

---

---

**Question: 15**

---

What CLI command is used to disable learning of incoming RIP routes on an interface?

- A. disable rip learning <VLAN>
- B. configure rip rxmode none <VLAN>
- C. configure rip interface <VLAN> passive
- D. None of these

---

**Answer: B**

---

---

**Question: 16**

---

Which statement is true? In a PC, the configured default gateway

- A. Is always within the PC IP (sub) network.
- B. Is always outside the PC IP (sub) network.
- C. Is always behind a router.
- D. Can be anywhere.

---

**Answer: A**

---

---

**Question: 17**

---

This type of OSPF router has its router interfaces connected into multiple OSPF areas.

- A. ASBR.
- B. ABR.
- C. DR.
- D. BDR.

---

**Answer: B**

---

---

**Question: 18**

---

Which CLI command would you use to configure the switch to ignore STP for selected VLANs?

- A. enable ignore-stp vlan <stpd>
- B. enable ignore-bpdu stpd <stpd> vlan <vlan>
- C. enable ignore-bpdu stpd <stpd>
- D. enable ignore-stp vlan <vlan>

---

**Answer: D**

---

---

**Question: 19**

---

Which of the following CLI commands would you use to enable ECMP for RIP?

- A. enable rip route sharing
- B. enable route sharing rip
- C. enable iproute sharing
- D. None of these, ecmp is not supported by RIP

---

**Answer: D**

---

---

**Question: 20**

---

If you wish to silently drop all traffic destined for IP network 100.219.10.0/24 with a gateway of 10.219.10.1/24 and without receiving any ICMP messages that would otherwise be generated, which CLI command would you execute?

- A. configure iproute delete 100.219.10.0/24 gateway 10.219.10.1
- B. configure iproute default 100.219.10.0/24
- C. configure iproute add blackhole 100.219.10.0/24 gateway 10.219.10.1
- D. configure iproute add blackhole 100.219.10.0/24

---

**Answer: D**

---

---

**Question: 21**

---

What is true when VLAN corporate shows a protocol field with the value of NONE.

- A. VLAN corporate will not forward any traffic.
- B. VLAN corporate must be a MAC-based VLAN.
- C. It is not possible for a VLAN to have NONE listed as the protocol.
- D. None of these.

---

**Answer: A**

---

## Thank You for trying EW0-200 PDF Demo

To Buy Latest EW0-200 Full Version Download visit link below

<https://www.certkillers.net/Exam/EW0-200>

## Start Your EW0-200 Preparation

**[Limited Time Offer]** Use Coupon “CKNET” for Further discount on your purchase. Test your EW0-200 preparation with actual exam questions.

<https://www.certkillers.net>