

## **Networks Extreme**

## EW0-300 Exam

**Networks Extreme Networks Specialist Exam** 

Thank you for Downloading EW0-300 exam PDF Demo

### You can Buy Latest EW0-300 Full Version Download

https://www.certkillers.net/Exam/EW0-300

#### Question: 1.

Extreme Networks "I" chipset switches allow you to run simultaneously the Radius and Tacacs+ features.

A. TRUE B. FALSE

Answer: B

#### Question: 2.

In a stable OSPF network, all OSPF routers in the same area must have the same LSDB contents.

A. True

B. False

#### Question: 3.

The IS-IS Routing Protocol has been developed in ISO to provide routing for pure OSI environments.

A. True

B. False

Answer: A

Answer: A

#### Question: 4.

Which of the following is the default ESRP priority setting for an Extreme switch?

A. 0

B. 1

- C. 254
- D. 255

Answer: A

#### Question: 5.

A TCP type ACL that uses the permit-established keyword filters out SYN packets in one direction.

A. TRUE

B. FALSE

Answer: A

#### Question: 6.

By default OSPF hello packets are sent out every:

A. 2 seconds.

- B. 10 seconds.
- C. 30 seconds.
- D. 40 seconds.

Answer: B

#### Question: 7.

What is an IGP protocol other than OSPF that uses the Dijkstra's SPF routing algorithm?

- A. RIP
- B. IS-IS
- C. EIGRP
- D. All of the above

Answer: B

#### Question: 8.

What does the abbreviation PIM stands for?

- A. Protocol Implicit Multicast
- B. Protocol Independent Multicast.
- C. Port Independent Multicast
- D. Port Implicit Multicast

Answer: B

#### Question: 9.

IP Version 6 has amongst other differences with IP version 4 also a different address length. What is the size of an Ipv6 address?

- A. 16 bits
- B. 32 bits
- C. 64 bits
- D. 128 bits

Answer: D

#### Question: 10.

An Ethernet Automatic Protection Switching (EAPS) domain relies on a control VLAN. That control VLAN must be tagged with an 802.1Q tag.

A. TRUE B. FALSE

Answer: A

#### Question: 11.

Select the statements that apply when you compare and differentiate VRRP and ESRP.

A. VRRP does not use the number of active ports as a criteria for Master election.

- B. VRRP can be enabled on VLAN default.
- C. VRRP and Spanning Tree can be enabled on the same switch and VLAN

D. All of the above

Answer: D

#### Question: 12.

The following MAC address, 00:00:5E:00:01:0A represents:

A. The MAC address used for ESRP, instance 01.

- B. The MAC address used for ESRP, instance 10.
- C. The MAC address used for VRRP, instance 01.
- D. The MAC address used for VRRP, instance 10.

Answer: D

#### Question: 13.

The Skew time in VRRP is used to ensure that two back-up routers do not switch to master state at the same time in case of a failover situation.

A. True B. False

**Answer:** A

Question: 14.

Within VRRP the election process of becoming the master switch takes place with the following precedence:

Step 1: The switch with the virtual router's IP address becomes the master switch.

Step 2: The switch with the highest VRRP priority becomes the master switch.

Step 3: The switch with the highest IP address becomes the master switch.

A. True B. False

Answer: A

#### Question: 15.

When limit-learning is configured on a port and the limit is reached the following traffic still flows to the port.

- A. Packets destined for the active Mac addresses
- B. Broadcast traffic
- C. EDP traffic
- D. All of the above

Answer: D

## Thank You for trying EW0-300 PDF Demo

To Buy Latest EW0-300 Full Version Download visit link below

https://www.certkillers.net/Exam/EW0-300

# Start Your EW0-300 Preparation

[Limited Time Offer] Use Coupon "CKNET" for Further discount on your purchase. Test your EW0-300 preparation with actual exam questions.

https://www.certkillers.net